

# HDC

## ON/OFF HIGHWAY DRIVE (HEAVY DRIVE CONSTRUCTION)

Stone ejection system reduces stone retention and casing penetration.



Aggressive, self cleaning tread pattern with lateral grooves provides excellent traction in all weather conditions both on and off the road.

New sidewall profile with curb rib reduces damage from curbing, cuts, and abrasions. Sidewall curb indicator provides warning when excessive sidewall scrubbing occurs.

Deep 30/32" cut resistant tread provides increased mileage and long wear with no speed restrictions.



### Applications:

Coal haulers, logging, construction, waste haulers, school buses and other on/off highway service.

## TIRE SPECIFICATIONS

Highway - 65 mph. at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
												lbs	psi	lbs	psi	
												(KG)	(KPa)	(KG)	(KPa)	
11R22.5*	H	30/32	0206906	05683000000	8.25	42.3 (1074)	11.1 (282)	12.2 (310)	19.6 (497)	12.5 (318)	488 (303)	130 (59)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	H	30/32	0206911	05683010000	8.25	44.3 (1125)	11.1 (282)	12.2 (310)	20.6 (522)	12.5 (318)	466 (290)	139 (63)	7160 (3250)	120 (830)	6610 (3000)	120 (830)

Note: Minimum Dual Spacing calculated without chains.  
These specifications subject to change without notice.

\*ECE Certified