

HDR

GENERAL PURPOSE DRIVE (HEAVY DRIVE REGIONAL)

Offset center tread blocks provide excellent all-weather traction.

Tapered tread grooves reduce stone retention for long casing life and multiple retreads.

Multi-service tread compound for local and long haul service.



Applications:

Drive position, short and long haul. On/off highway service (depending on conditions).

TIRE SPECIFICATIONS

Highway - 65 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
												lbs	psi	lbs	psi	
												(KG)	(KPa)	(KG)	(KPa)	
245/70R19.5*	H	20/32	0206086	04755360000	6.75	33.3 (846)	9.8 (249)	10.2 (259)	15.3 (389)	11.0 (279)	622 (387)	73 (33)	4940 (2240)	115 (790)	4675 (2120)	115 (790)
12R22.5*	H	26/32	0206146	05755770000	9.00	43.3 (1100)	12.2 (310)	11.7 (297)	19.8 (503)	13.5 (343)	481 (299)	142 (64)	7830 (3350)	120 (830)	6940 (3150)	120 (830)
315/80R22.5*	J	26/32	0215767	05757190000	9.00	42.8 (1086)	12.3 (312)	12.9 (328)	19.8 (503)	13.8 (351)	484 (300)	142 (64)	8820 (4000)	130 (900)	7385 (3350)	130 (900)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.

*ECE Certified
315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs.