

HSC

ALL-POSITION ON/OFF HIGHWAY SERVICE (HEAVY STEER CONSTRUCTION)

New sidewall profile with curb rib reduces damage from curbing, cuts and abrasions.

Stone ejection system reduces stone retention and casing penetrations.

Visual Alignment Indicators (VAI®) alert user to tire tracking problems.

23/32" tread depth and cut/chip resistant tread compound provide long tread life in on/off road conditions.

Applications:

Coal haulers, logging, construction, waste haulers, school buses and other on/off highway service.



TIRE SPECIFICATIONS Highway - 75 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													Single	psi	Dual	psi
11R22.5*	H	23/32	0238460	05683870000	8.25	41.9 (1062)	11.1 (282)	12.2 (310)	19.6 (497)	12.5 (318)	494 (308)	126 (57)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	H	23/32	0238465	05683880000	8.25	43.8 (1113)	11.1 (282)	12.2 (310)	20.6 (523)	12.5 (318)	473 (294)	132 (60)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
12R22.5*	H	23/32	0238473	05683890000	9.00	42.9 (1090)	12.4 (315)	13.7 (347)	20.2 (512)	13.5 (343)	483 (301)	129 (59)	7390 (3350)	120 (830)	6780 (3075)	120 (830)
12R24.5	H	23/32	0238476	05683900000	9.00	45.0 (1144)	12.4 (315)	13.7 (347)	21.2 (539)	13.5 (343)	460 (286)	136 (63)	7830 (3550)	120 (830)	7160 (3250)	120 (830)
12.00R20*	J	23/32	0282194	05351240000	8.50	44.2 (1123)	12.3 (312)	13.6 (345)	20.3 (516)	13.5 (343)	470 (292)	160 (73)	8270 (3725)	120 (830)	7390 (3350)	120 (760)
12.00R24*	L	18/32	0282197	05353460000	8.50	47.2 (1199)	12.3 (312)	13.5 (343)	22.3 (566)	14.1 (358)	464 (288)	161 (73)	9920 (4500)	120 (830)	8820 (4000)	120 (830)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.

*ECE Certified

Form #: SS-HSC 01/03 ©Continental Tire North America, Inc. 2003