

HSL Eco Plus

PREMIUM LONG HAUL STEER (HEAVY STEER LONG HAUL)

Equal rib widths provide even pressure distribution resulting in more resistance to irregular wear.

Unique button and ramp stone ejection system helps eliminate stone retention.

Visual Alignment Indicators (VAI®) alert user to tire tracking problems.

Shoulder protection rib resists irregular shoulder wear.



18/32" 6 rib tread design provides long mileage and low rolling resistance.

Applications:

Long haul and over the highway steering and all-position use.

TIRE SPECIFICATIONS Highway - 75 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
													lbs	psi	lbs	psi
													(KG)	(KPa)	(KG)	(KPa)
11R22.5*	H	18/32	0239006	05683830000	8.25	41.4 (1052)	11.0 (278)	12.2 (310)	19.4 (493)	12.5 (318)	500 (311)	116 (53)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	H	18/32	0239012	05683840000	8.25	43.4 (1102)	11.0 (278)	12.2 (310)	20.4 (518)	12.5 (318)	475 (295)	125 (57)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
275/80R22.5*	H	18/32	0239020	05683850000	8.25	40.1 (1019)	11.2 (280)	12.2 (310)	18.7 (475)	12.5 (318)	515 (320)	111 (50)	6940 (3150)	120 (830)	6175 (2800)	120 (830)
285/75R24.5	H	18/32	0239036	05683860000	8.25	41.4 (1052)	11.0 (278)	11.9 (302)	19.3 (490)	12.5 (318)	500 (311)	116 (53)	6780 (3075)	120 (830)	6175 (2800)	120 (830)
315/80R22.5* **	J	18/32	0225934	05716400100	8.25	42.4 (1076)	12.3 (312)	12.9 (328)	19.7 (500)	13.8 (351)	489 (304)	144 (65)	8270 (3750)	120 (830)	7610 (3450)	120 (830)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.

*ECE Certified
**Tread Pattern May Vary