

ALL-POSITION ON/OFF HIGHWAY SERVICE

Multi-service tread pattern provides good mileage on-highway and traction in off-highway service.

Thick undertread resists casing penetration and damage for multiple retread opportunities.

Cut and tear resistant tread compound provides excellent on/off highway service.



Applications

Coal haulers, logging, construction, school buses, waste haulers, any on/off highway service.

TIRE SPECIFICATIONS

Highway - 65 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE lbs (KG)	psi (KPa)	DUAL lbs (KG)	psi (KPa)
10.00R20*	H	20/32	0111236	05391060000	7.50	41.4 (1052)	10.8 (275)	11.1 (283)	19.1 (485)	12.6 (319)	500 (310)	131 (59)	6610 (3000)	120 (830)	6005 (2625)	120 (830)
11.00R20*	H	23/32	0111228	05391090000	8.00	42.6 (1082)	11.3 (286)	12.0 (304)	19.6 (498)	13.4 (341)	486 (302)	137 (62)	7390 (3350)	120 (830)	6780 (3075)	120 (830)
11.00R22*	H	23/32	0111201	05391100000	8.00	44.6 (1132)	11.3 (286)	12.0 (304)	21.6 (549)	13.4 (341)	464 (288)	158 (71)	7830 (3550)	120 (830)	7160 (3250)	120 (830)
11.00R24*	H	23/32	0237574	05390130000	8.00	46.9 (1191)	11.6 (295)	12.5 (318)	21.7 (551)	13.2 (335)	442 (275)	159 (72)	8270 (3750)	120 (830)	7610 (3450)	120 (830)
10R22.5	G	19/32	0237584	05680000000	7.50	40.1 (1019)	10.0 (254)	10.8 (274)	18.5 (470)	11.4 (290)	516 (321)	100 (45)	5675 (2575)	115 (790)	5355 (2430)	115 (790)
11R22.5*	H	20/32	0237638	05759160000	8.25	41.6 (1057)	11.0 (279)	11.9 (302)	19.2 (488)	12.5 (318)	498 (310)	114 (52)	6610 (3000)	120 (830)	6005 (2625)	120 (830)
11R24.5	H	20/32	0237644	05680450000	8.25	43.6 (1107)	11.0 (279)	11.9 (302)	20.2 (513)	12.5 (318)	475 (295)	122 (55)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
12R22.5*	H	23/32	0237702	05759630000	9.00	42.9 (1090)	11.8 (300)	12.7 (323)	19.9 (505)	13.5 (343)	482 (300)	132 (60)	7390 (3350)	120 (830)	6780 (3075)	120 (830)
12R24.5	H	23/32	0237744	05680550000	9.00	44.9 (1140)	11.8 (300)	12.7 (323)	20.8 (528)	13.5 (343)	461 (287)	140 (64)	7830 (3550)	120 (830)	7610 (3250)	120 (830)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.

*ECE Certified.