

D450

PREMIUM DRIVE

Innovative tread pattern that has proven superior in reducing stone retention.

Open shoulder design provides excellent traction.

Advanced tread compound for long original mileage.



Applications

Single and tandem axle, long and short haul, over-the-highway drive position.

TIRE SPECIFICATIONS Highway - 75 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
													lbs	psi	lbs	psi
													(KG)	(KPa)	(KG)	(KPa)
11R22.5	G	26/32	0236900	05680050000	8.25	41.7 (1059)	11.3 (287)	12.1 (307)	19.5 (495)	12.5 (318)	494 (307)	122 (55)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
11R22.5	H	26/32	0236916	05680060000	8.25	41.7 (1059)	11.3 (287)	12.1 (307)	19.5 (495)	12.5 (318)	494 (307)	123 (56)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	G	26/32	0236934	05680490000	8.25	43.7 (1110)	11.3 (287)	12.2 (310)	20.5 (521)	12.5 (318)	472 (293)	131 (59)	6610 (3000)	105 (720)	6005 (2725)	105 (720)
11R24.5	H	26/32	0236993	05681070000	8.25	43.7 (1110)	11.3 (287)	12.2 (310)	20.5 (521)	12.5 (318)	472 (293)	132 (60)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
295/75R22.5	G	26/32	0236938	05680870000	8.25	40.5 (1029)	11.5 (292)	12.2 (310)	18.8 (478)	12.5 (318)	510 (317)	119 (54)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
285/75R24.5	G	26/32	0236942	05680660000	8.25	41.7 (1059)	11.2 (284)	12.1 (307)	19.4 (493)	12.5 (318)	494 (307)	124 (56)	6175 (2800)	110 (760)	5675 (2575)	110 (760)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.