

D460

PREMIUM DRIVE

Innovative tread pattern minimizes stone retention providing excellent retreadability.

Closed shoulder tread design promotes even tread wear.

Advanced tread compound for long mileage.



Applications

Tandem drive axle for long and short over-the-road use.

TIRE SPECIFICATIONS Highway - 75 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
													lbs	psi	lbs	psi
													(KG)	(KPa)	(KG)	(KPa)
11R22.5	G	26/32	0236208	05681080000	8.25	41.7 (1059)	11.3 (287)	12.1 (307)	19.5 (495)	12.5 (318)	494 (307)	124 (56)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
11R22.5	H	26/32	0236214	05681090000	8.25	41.7 (1059)	11.3 (287)	12.1 (307)	19.5 (495)	12.5 (318)	494 (307)	125 (57)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	G	26/32	0236217	05681100000	8.25	43.7 (1110)	11.3 (287)	12.2 (310)	20.5 (521)	12.5 (318)	472 (293)	132 (60)	6610 (3000)	105 (720)	6005 (2725)	105 (720)
11R24.5	H	26/32	0236195	05682030000	8.25	43.7 (1110)	11.3 (287)	12.2 (310)	20.5 (521)	12.5 (318)	472 (293)	134 (61)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
295/75R22.5	G	26/32	0236233	05681110000	8.25	40.5 (1029)	11.5 (292)	12.2 (310)	18.8 (478)	12.5 (318)	510 (317)	119 (54)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
285/75R24.5	G	26/32	0236236	05681120000	8.25	41.7 (1059)	11.2 (284)	12.1 (307)	19.4 (493)	12.5 (318)	494 (307)	125 (57)	6175 (2800)	110 (760)	5675 (2575)	110 (760)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.