

LMT 400

ALL-POSITION SERVICE/TRACTION DRIVE

All position, 16/32 tread pattern provides long mileage in regional local service.

Button/Rib tread design provides excellent traction and handling.

Closed shoulder tread design provides even wear and reduce noise.



Applications

Commercial Duty light trucks
OE on Ford F450 and F550.

TIRE SPECIFICATIONS Highway - 81 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
												lbs (KG)	psi (KPa)	lbs (KG)	psi (KPa)	
225/70R19.5*	F	16/32	0159948	05682410000	6.00	31.9 (810)	8.2 (208)	9.3 (236)	14.9 (378)	10.0 (254)	649 (403)	58 (26)	3640 (1655)	95 (655)	3415 (1552)	95 (655)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.

*ECE Certified