

LMT 460

ALL-POSITION SERVICE

All position, 18/32 tread pattern provides excellent traction and handling in both on and off road conditions.

Button/Rib tread design provides excellent traction and handling.

Closed shoulder tread design provides even wear and reduced noise.



Applications

Commercial duty light trucks.

TIRE SPECIFICATIONS Highway - 81 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED	OVERALL INFLATED	LOADED SECTION	STATIC LOADED	MINIMUM DUAL	REVS PER MILE	TIRE WEIGHT	MAX LOAD@INFLATION			
						DIAMETER IN (mm)	WIDTH IN (mm)	WIDTH IN (mm)	RADIUS IN (mm)	SPACING IN (mm)	(KM)	LB (KG)	lbs (KG)	psi (KPa)	lbs (KG)	psi (KPa)
255/R7019.5*	F	18/32	0159922	0568240000	6.00	32.0 (813)	8.2 (208)	9.3 (236)	15.0 (381)	10.0 (254)	647 (402)	60 (27)	3640 (1655)	95 (655)	3415 (1552)	95 (655)

Note: Minimum Dual Spacing calculated without chains. These specifications subject to change without notice.

*ECE Certified.