


# RIB ST


## PREMIUM TRAILER

Stone ejection system reduces stone retention and casing penetration.



Wide tread arc enhances tire stability and contributes to long mileage – accepts wider (8”) recap.

Visual Alignment Indicators (VAI®) alert user to tire tracking problems.



Reduced tread depth minimizes tread squirm and irregular tread wear.



### Applications

Trailer and free-rolling positions, steer position (depending on conditions).

## TIRE SPECIFICATIONS Highway - 75 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE lbs (KG)	psi (KPa)	DUAL lbs (KG)	psi (KPa)
11R22.5	G	13/32	0237086	05680100000	8.25	41.1 (1045)	11.1 (281)	12.0 (306)	19.1 (486)	12.5 (318)	503 (312)	104 (47)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
11R22.5	H	13/32	0236892	05683490000	8.25	41.1 (1045)	11.1 (281)	12.0 (306)	19.1 (486)	12.5 (318)	503 (312)	106 (48)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	G	13/32	0237094	05680430000	8.25	43.1 (1094)	11.0 (280)	12.0 (305)	20.0 (509)	12.5 (318)	481 (298)	112 (50)	6610 (3000)	105 (720)	6005 (2725)	105 (720)
11R24.5	H	13/32	0236896	05683500000	8.25	43.1 (1094)	11.0 (280)	12.0 (305)	20.0 (509)	12.5 (318)	481 (298)	114 (51)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
295/75R22.5	G	13/32	0239810	05682950000	8.25	39.7 (1009)	11.0 (279)	12.0 (304)	18.5 (469)	12.2 (311)	521 (323)	102 (46)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
285/75R24.5	G	13/32	0237019	05681960000	8.25	41.1 (1045)	10.7 (273)	11.7 (298)	19.1 (486)	12.5 (318)	503 (312)	104 (47)	6175 (2800)	110 (760)	5675 (2575)	110 (760)

Note: Minimum Dual Spacing calculated without chains.  
These specifications subject to change without notice.